

PREGLED BETONA IZ PONUDE

TRANSPORTNI BETONI 0-32 mm		
KLASA ČVRSTOĆE	KLASA IZLOŽENOSTI	KLASA KONZISTENCIJE
C8/10 (MB-10)	X0	S2
C12/15 (MB-15)	X0	S2
C16/20 (MB-20)	X0	S2
C20/25 (MB-25)	XC1	S2
C25/30 (MB-30)	XC2	S2
C30/37 (MB-40)	XC4,XD2,XA1	S2

PUMPANI BETONI 0-32 mm		
C16/20 (MB-20)	X0	S3
C20/25 (MB-25)	XC1	S3
C25/30 (MB-30)	XC2	S3
C25/30 (MB-30)	XC2,VDP-2	S4
C30/37 (MB-40)	XC4,XD2,XA1	S3
C30/37 (MB-40)	XC4,XD2,XA1 VDP-2	S4

TRANSPORTNI BETONI 0-16 mm		
KLASA ČVRSTOĆE	KLASA IZLOŽENOSTI	KLASA KONZISTENCIJE
C8/10 (MB-10)	X0	S2
C12/15 (MB-15)	X0	
C16/20 (MB-20)	X0	S2
C20/25 (MB-25)	XC1	S2
C25/30 (MB-30)	XC2	S2
C30/37 (MB-40)	XC4,XD2,XA1	S2

PUMPANI BETONI 0-16 mm		
C16/20 (MB-20)	X0	S3
C20/25 (MB-25)	XC1	S3
C25/30 (MB-30)	XC2	S3
C25/30 (MB-30)	XC2,VDP-2	S4
C30/37 (MB-40)	XC4,XD2,XA1	S4
C30/37 (MB 40)	XC4,XD2,XA1,VDP2	S4
C35/45 (MB-45)	XC4,XD3,XA1	S4
C40/50 (MB-50)	XC4,XD3,XA1	S4

BETONI OTPORNI NA MRAZ I SOL		
Dmax=32 mm		
C30/37 (MB-40)	XC4,XD2,	S4
	XF4,XA1	
Dmax=16 mm		
C25/30 (MB-30)	XC2,XF2	S4
C30/37 (MB-40)	XC4,XD2,XF4,XA1	S4
C35/45 (MB-45)	XC4,XD3,XF4,XA1	S2
C40/50 (MB-50)	XC4,XD3,XF3,XF4,XA1	S4
C50/60 (MB-60)	XC4,XD3,XF3,XF4,XA1	S4

PREGLED BETONA IZ PONUDE

DIJAFRAGMA		
Dmax=16 mm		
C25/30 (MB-30)	XC2	S4
C30/37 (MB-40)	XC4,XD2	S4
C35/45 (MB-45)	XC4,XD3	S4

ZEMLJOVLAŽNI BETONI	
Dmax=32 mm	Dmax=16 mm
C12/15 (MB-15)	C12/15 (MB-15)
C16/20 (MB-20)	C16/20 (MB-20)
C20/25 (MB-25)	C20/25 (MB-25)
C25/30 (MB-30)	C25/30 (MB-30)

LAGANI BETON (MEPS)
Masa betona (kg)
1200
1000
800

GLAZURA
Dmax=4mm

MIKROBETON
Dmax=8 mm
C16/20 (MB-20)
C20/25 (MB-25)
C25/30 (MB-30)
C30/37 (MB-40)

MLAZNI BETON
Dmax=8 mm
Dmax=4 mm

CEMENTNA STABILIZACIJA
Dmax=45 mm
Dmax=32 mm